

# Universal Tile Vent



## Installation

The Tile Vent is positioned in-line with the tile below and an opening is cut in the underlay using the template provided. Once the opening has been made in the underlay the back box is inserted through the opening until the Tile Vent nibs are

located over the top of the batten. The Tile Vent is then fixed into the batten through the nail hole within the Tile Vent and with the wire clip provided. The front skirt is dressed onto a clean dry tile surface. The roof tiles either side of the vent are then laid. Prior to the tile above the vent being laid the upper skirt needs to be pushed down. Tile battens would need to be cut if plain tiles are being used.

## Regulations and certifications

Complies fully with relevant Building Regulations and British Standards.

A Universal Tile Vent that suits most concrete interlocking roof tiles that can be used to ventilate roof voids or as a terminal for soil and ventilation pipes and mechanical extraction systems.

## Product features & benefits

- Low profile design
- Choice of five colours
- Fully wind tunnel tested
- Built in downpipe allows direct ventilation to roof space
- Adaptor available for soil ventilation or mechanical extraction
- Adaptor available for 125 mm diameter ducting

## Area of application

Suitable for:

- Most popular interlocking and plain tile roofs with a pitch over 17.5°
- Roof space ventilation or for soil ventilation or mechanical extraction when used with the soil/mechanical adaptor
- High or low level roof ventilation

## Material

Soft and rigid UPVC

## Colours / Product Codes

Antique red	KG985403
Brown	KG985436
Slate grey	KG985430
Terracotta	KG985434
Black	KG985476

## Dimensions / Weight (per carton)

455 mm long x 440 mm wide x 91 mm deep (excluding downpipe) / 18.9kg

## Packaging

10 bases, caps per carton

## Related products

Soil mechanical adaptor + 100/100mm Flexipipe	KG979800
Soil mechanical adaptor to suit 100mm	KG968300
Soil mechanical adaptor to suit 100mm/125mm	KG979000
Flexipipe 100/100mm	KG979900
Flexipipe 100/125mm	KE8047

**Note:** The Uni-Line Tile Vent does not suit the following tile profiles: Redland Delta, Cambrian, Saxon, Richmond; Anchor Centurion, Slate; Marley Monarch; Clay Pantiles; Landmark Slates

## PERFORMANCE / TECHNICAL DATA

Provides 15,000mm<sup>2</sup> effective vent area

Vent spacing

5mm opening at 3m centres  
10mm opening at 1.5m centres  
25mm opening at 0.6m centres

Airflow resistance Universal Tile Vent **with 100mm pipe adaptor**

15 litres/sec	30 litres/sec	60 litres/sec
4 Pascals	16 Pascals	65 Pascals

Airflow resistance Universal Tile Vent **with 125mm pipe adaptor**

15 litres/sec	30 litres/sec	60 litres/sec
3 Pascals	12 Pascals	47 Pascals

Klober Ltd

Unit 6F · East Midlands Distribution Centre · Short Lane · Castle Donington · Derbyshire · DE74 2HA  
Tel. +44 (0)1332 813 050 · Fax +44 (0)1332 814 033 · info@klober.co.uk · www.klober.co.uk

**KLOBER**